



Mortuary Equipment

CONTACT DETAILS

Tel no. 013 244 2119
Cell no. 072 446 4043
Fax no. 086 528 7895
Email: stefus@amoret.co.za

3 Bosberg Crescent
Aerorand
Middelburg
1050

Postnet Suite MW177
Private Bag x1838
Middelburg
1050

INDEX

	Page:
Autopsy Saws	4
Examination Lights	4 – 5
Headlights	5
Hospital Holloware	6
Medical & Surgical Instruments	6
Mortuary Body Handling Equipment	7
Refrigerators & Freezers	8
Scales	9
Sterilizers / Autoclave	9 – 10
Sterilizers/Autoclaves Accessories	10
Suction Units	11 – 12

AUTOPSY SAWS

De Soutter



- The safe hand piece is fully immersible allowing it to be routinely scrubbed and disinfected after use
- Variable speed from zero to maximum operated at the power supply gives optimum cutting efficiency
- Degree of protection of saw hand piece against ingress of liquid is IP67 immersible at 1 meter
- The extractor has five levels of filtration enabling the system to meet the highest health standards

Hercules Electrical



- Heavy duty blade: special hardening for synthetic cast material
- High power & quality
- Overload system
- Maximum durability
- Maintenance free
- Robust construction
- Weight: 1.6kg
- Voltage: 220V
- 150W motor, 14 000RPM and electronic suppressed

EXAMINATION LIGHTS

ALI-HL1220-PP



- Non-magnetic stainless steel central tubes
- Reinforced nylon base with 5 feet
- Mobile on twin wheel swivel castors (diameter of 50 mm)
- Flexible goose neck arm: 700 mm
- Step down transformer 230V, 50W
- Halogen Bulb 12 V, 35 W, 10° angle of emission with UV block
- Input voltage: 220/230V 50-60Hz
- Knock down construction

Wall Mounted



- Illumination Intensity : 40000 Lux
- Colour Temperature : 6000-6500 K
- Colour rendering index : 75 (Ra)
- Spot diameter : 150mm
- Light Field Diameter : D 30 cm = 18 cm
- Temperature Rise of Field : 0 (°C)
- Power Supply : 220 V / 50 Hz. AC
- Extension : 75 cm goose neck
- Specification of Bulb : LED 6 bulbs (high power)
- Brightness Control : Available

HEADLIGHTS

Welch Allyn



- Weighing approximately 113g, it's one of the most comfortable and light weight headlights available
- Fits inside a shirt pocket and allows complete freedom of movement
- Supplies bright, white, shadow-free light for true tissue colour
- Solid state lamp has 10,000-hour life expectancy with minimal degradation of light output

MD-750



- Ergonomic head band which is padded and fully adjustable in circumference and height
- Head band cleaning made easier with removable and washable padding
- Double lens precision optical with adjustable holder to focus light point
- Illumination axis adjustable over a wide range
- 3.5mm fiber optic bundle cable with a length of 2.3m
- Connector for use with other manufacturer's projectors are available

HOLLOWWARE

- wide variety available on request



MEDICAL & SURGICAL INSTRUMENTS

- A wide variety available on request



MORTUARY BODY HANDLING EQUIPMENT

Equipment for use in Mortuaries and Funeral Homes.

For Cadaver lifting and transport

- Manual and electric lifting trolleys.
- Transport trolleys
- Covered transport trolleys.
- Washing, preparation and embalming tables.
- Replacement body trays and racking.



Transport trolley with cover



Body tray 550mm and 650mm width available



Electric lifting trolley

REFRIGERATORS, FREEZERS AND COLD ROOMS

Refrigerated mortuary cabinets



- With a range of finishes and features to suit every budget, e.g. 3 or 6 tier
- Easy to clean and maintain, featuring fully removable refrigeration system and stainless steel body trays
- Cooler and freezer versions available

Mortuary cold rooms

Mortuary cold rooms and Freezer rooms with specialized racking system and body trays for Hospitals, Mortuaries and Funeral Parlours.



- These systems provide an economical storage facility where large numbers of cadavers have to be stored.
- Our mortuary fridges are available in different finishes, materials and configurations to suit every budge

SCALES

Adam CBK4



- Durable construction and versatility make the CBK unmatched for value in industrial weighing.
- Serving a variety of applications the CBK includes basic weighing,
- check weighing with LED limit indicators and parts counting.
- Full featured and easy-to-use, the CBK is the right choice for industry when flexibility matters.
- Reliable performance

STERILIZERS / AUTOCLAVES

Automatic Sterilizer SA-232



- European Class N standard
- Capacity: 16L
- Overall dimensions: 600mm x 335mm x 430mm
- Gross weight: 15.5 kg
- Power supply: 230V/50~60Hz or 110V/50~60Hz
- Power consumption: 230V / 7amp heater 1 400W
- 110V / amp heater 1 200W
- Sterilizing temperature: 122°C
- For wrapped and unwrapped solid instruments

Sturdy SA-232x





- European Class N standard
- Capacity: 16L
- Overall dimensions: 501mm (W) x 406mm(H) x 537mm(D)
- Chamber size: 230mm x 410mm
- Power consumption: 220V-240V/1.4KW (max.) / 7A – 110V/1.2KW (max.) 11A
- Sterilizing temperature: 140°
- For wrapped and unwrapped solid instruments

Class B



- European Class B standard
- 3 Times vacuum preceding vacuum drying
- Residual humidity is <0.2%
- Vacuum measurement reaches -0.70bar
- Sterilizing temperature: 121 °C - 134 °C
- Water steam reaches every corner
- It measures the penetration of water steam (installed with Bowie & Dick test)
- For wrapped and unwrapped, solid and hollow instruments

STERILIZERS / AUTOCLAVES ACCESSORIES



SUCTION UNITS

Gabler Suction Unit



- Sturdy, well-balanced and fully mobile on 5 castors
- Robust, light-weight vacuum formed ABS housing
- Routine maintenance free suction pump and motor
- Fitted with a change-over switch for easy changing between bottles
- Easy and reliable operation
- Bacterial filters fitted to both inlets to the pump
- Highly visible vacuum gauge located next to vacuum control knob

Askir 30



- Mobile and portable with a weight of ± 3.6 kg
- Also available as table device
- Mains-powered device
- Used for minor surgeries as well as nasal, oral and tracheal aspiration
- Maximum 120 minutes operation time, then 60 minutes cooling time
- Ideal for the home as it is light to transport
- Satisfies all current norms and EU safety standards
- Comes with a 1 litre autoclavable plastic collection jar, overflow valve, suction control, vacuum display, connection tube, suction catheter and antibacterial filter
- The stand model comes with 2 x 2 litre autoclavable plastic collection jars

Askir C30



- Easily portable equipment designed on stand with mobile castor wheels. Intermittent duty cycle at 35°C and 110% operating voltage, 120 min ON / 60 min OFF
- A series of LED's on the front control panel signals whether the machine is operating
- Made of highly heat resistant, electrically insulated plastic material in conformity with the latest European safety standards
- Supplied with a polycarbonate 2 x 2 litre autoclavable vessel complete with overflow valve
- Equipped with aspiration regulator, located on the front panel

Hospivac 350



- New Hospivac 350 is a surgical aspirator working with 230V ~ / 50 Hz network electricity
- Four antistatic wheels with two brakes and a movement handle
- Easily moveable and designed for virtually continuous use
- The product is supplied with 2 x 2 litre polycarbonate autoclavable jars with overflow valve
- Equipped with aspiration regulator and vacuum indicator located on the front panel
- Power consumption: 230VA
- Fuse 1 x 4 A 250V
- ISO 10079-1 High Vacuum/High Flow
- Maximum suction aspiration: -0.90 Bar
- Maximum suction flow: 60 l/min
- Dimensions: 460mm(l) x 600mm(h) x 420mm(w)

Gabler Mobile Electric High Vacuum Suction



- Robust, light-weight vacuum formed ABS housing
- Sturdy, well-balanced and fully mobile on 5 castors
- Routine maintenance free suction pump and motor
- Fitted with a change-over switch for easy changing between bottles
- Easy and reliable operation
- Bacterial filters fitted to both inlets to the pump
- Highly visible vacuum gauge located next to vacuum control
- Maximum vacuum: -83kPa (625mmHg)
- Suction capacity: 26 litres per minute
- Collection jars fitted with 2 suction bottles, each with a capacity of 1800ml and graduated to 1500ml in 100ml steps
- Dimensions approx.: 54cm (w) x 75cm (h) x 75cm (d)

Sms Wall Mounted Suction



- Vacuum regulator: Pipeline operated 0-minus 100kPa
- Steplessly controlled diaphragm
- Diaphragm: Viton rubber with stainless high pressure spring
- Gauge: 1/8th BSP Bottom entry, 0 minus 100 kPa
- Vacuum Source Connection: ¼ BSP Elbow with tailpiece
- Inlet: 1/8th BSP Straight tailpiece 6mm for attachment to liner